

PRODUCT SHEET & SPECIFICATIONS

EXPOSED CEILING PLATE MAIN UNIT (DIRECT FIRED) MODEL LG035-M6/M4

TYPICAL APPLICATIONS FOR THIS SERIES

For use when a direct fired speaker is required or where a sheetrock or gypsum ceiling is in place and where speaker grills can be installed flush to the ceiling. Available height 6" and 4" models. All Lencore Sound Masking Systems are custom designed to meet local codes and to fit a variety of site conditions and applications in:

- + Open Plan
- + Closed Plan
- + Retrofit
- + New Construction

The units were developed for sheetrock®/gypsum ceilings. The speaker unit has an extended painted grill face with screw adjustments for mounting to the ceiling.



The Lencore Spectra® Sound Masking LG035-M6 is the main unit to the LG035-S6 and duplicates the output of the main. Each main unit consists of an individual self-contained noise generator, audio amplifier, loudspeaker in a damped metal enclosure, powered by 16/18 volts AC transformer and is capable of driving two secondary models.

Each main unit is solid state and consists of a CMOS/MSI digital random sequence noise generator, electronic amplifier and filter for active spectrum shaping, and is equipped with a 10-step volume control plus an additional continuous volume control. For ease of tuning this volume control is located behind the exposed grill and adjustable from the underside of the ceiling. Range of sound level: 41-86 dBA (measured at 1.5 feet from speaker). Additionally contained is a continuous and completely separate volume control for paging/music.

The masking system can be uniquely adjusted to suit a variety of standard and non-standard ceiling conditions by making adjustments to the amplitude and spectra shapes. This adjustment can be made in increments of +/- ½ dB. In addition, the system has the adjustment capability to provide the most unobtrusive sound while obtaining the maximum speech privacy that meets ASTM

E-1130 standards for speech privacy and sound uniformity. The spectrum shape adjustment ranges from 1 dB at 125 Hz to 20 dB at 8,000 Hz (typical).

The Spectrum Graph on following page (measured in A-scale) depicts the range of spectra attained with standard fiberglass or mineral ceiling tile. The lower spectra provide the most unobtrusive sound, while the upper spectra provide the maximum speech privacy.

Lencore's Spectra® System can incorporate a high-quality paging and music system to handle all call paging, zoned paging, voice over IP, paging through the phone system, security and life safety paging.

Lencore's Spectra® can work in conjunction with Lencore's SPEC™ software program which serves as a diagnostic and planning tool for sound masking and paging systems to qualify and analyze the acoustical performance levels of your space, enabling a fact-based approach to predicting spatial and temporal uniformity of sound for sound masking.

*Sheetrock is a registered trademark of USG Interiors, Inc.

EXPOSED CEILING PLATE MAIN UNIT (DIRECT FIRED)

– ENCLOSURE:

- + Aluminum Housing
- + Metal Screen, White With Perforated Grill (8")
- + Lightweight Mounting Chain
- + Height: 6" LG035-M6 6" LG035-M4
- + Diameter: 6" LG035-M6 6" LG035-M4
- + Weight: 3 ½ lbs. LG035-M6 3 ½ lbs. LG035-M4

– LOUDSPEAKER:

- + 5-inch-wide dispersion
- + Power Rating: 10 watts RMS
- + Frequency Response: 50-12,000 Hz
- + Pressure/Sensitivity: SPL – at 1 watt/m-90dB
- + Impedance: 16 Ohms
- + Resonance: 82 Hz
- + Magnet Weight: 10 oz.
- + Magnet Structure Weight: 26 oz.
- + Cone: Formed Fiber
- + Cone Suspension: High Compliance Foam
- + Voice Coil: 1-inch diameter
- + Voice Coil Form: Anodized Aluminum


– GENERAL SPECIFICATIONS:

- + Paging Input: 25v RMS at 12.5mW (50kOhms)
- + Power Requirement: 16v/18v AC, 60 Hz at 50mA (typical no page)
- + With Paging: Up to 200mA
- + Output Adjustment: 15dB step-volume control
- + Additional continuous control (56-86 dBA total), plus a central volume control that can control up to 50 masters for an additional attenuation of 15dB
- + System can be tuned to +/- ½ dB

– WIRE REQUIREMENT:

18 gauge, plenum rated non-shielded 2, 4 or 6 conductor depending on application

– SPECTRUM GRAPH



MASKING/PAGING UNITS ARE UL LISTED FOR USE IN AIR HANDLING SPACES

OTHER SYSTEMS ALSO AVAILABLE

Spectra i.Net™ (Networked), CrossNetOne™ (Networked), CrosswaysOne™
In-plenum and direct fired all available with paging/music.