

SPECTRA – i.Net®

PRODUCT SHEET & SPECIFICATIONS

STANDARD SPEAKER ENCLOSURE (MODEL GP19gsa/GP85gsa)



Note: The speakers above are shown painted. Standard speakers come in an aluminum finish. Custom painting is available at an upcharge.

FUNCTION

What makes Lencore's new Spectra i.Net® system intelligent is its intuitive technology and its infinite flexibility on an open-platform system to suit any project size. The combined innovations of the complete sound masking system – sound source, speakers, power supply; i.LON®, music page interface, equalizers, online Sound Manager control and one-touch remote control put the Spectra i.Net™ system on a new level of customization and performance.

The Spectra i.Net® system is the most sophisticated masking system available when a network system is required. The system features fast, complete control over every sound frequency for masking. Extreme design flexibility, plus, easy system expansion with the addition of sound sources and speakers to the network. Sound control with the click of the remote or mouse, even off-site. Preferred, award-winning sound quality, only from Lencore's Systems.

Speakers are configured with integrated RJ12 connections for plug & play and ease of installation.

Model

GP19gsa
GP85gsa

DIRECT FIRED SPEAKER ENCLOSURE

– SPEAKER ENCLOSURE

- + Aluminum Housing
- + Grill Cover: Galvanized perforated grill
- + Lightweight Mounting Chain
- + Two speaker models available – 6" & 4"

– SPEAKER MODEL DIMENSIONS

G19gsa

- Height – 6"
- Diameter – 6"
- Weight – 3lbs

G85gsa

- Height – 4"
- Diameter – 6"
- Weight – 3lbs

– LOUDSPEAKER

- + 5-inch - wide dispersion
- + Power Rating – 10 watts RMS
- + Frequency Response – 50 – 12,000 Hz
- + Impedance – 32 Ohms
- + Resonance – 80 Hz
- + Magnet Weight – 10 oz
- + Magnet Structure Weight – 26 oz
- + Cone – Formed Fiber
- + Cone Suspension – High Compliance Foam
- + Voice Coil – 1-inch diameter
- + Voice Coil Form – Anodized Aluminum

– PAGING INPUT

- + Via OP and MPI

– POWER REQUIREMENT

- + Powered by OP

– OUTPUT ADJUSTMENT

- + N/A

– WIRE REQUIREMENTS

- + All wire must be plenum rated and UL listed
- + Speakers use Cat 5e or equivalent, 3 twisted pair and RJ12 connectors
- + Crossover wire: Pin 1 to Pin 6, Pin 2 to Pin 5, etc.

– OTHER SYSTEM WIRE REQUIREMENTS

- + 16 gauge, plenum rated, stranded, 2-conductor wire (for power supply to OP)
- + Cat 5e cable, 3 twisted pair, with standard RJ12 connectors
3 twisted pair (audio cable and speaker cable)

MASKING/PAGING UNITS ARE UL LISTED FOR USE IN AIR HANDLING SPACES

OTHER SYSTEMS ALSO AVAILABLE

Spectra®, CrossNetOne™, CrosswaysOne™