

# Lencore

THE LEADING MANUFACTURER OF SOUND MASKING SYSTEMS.

A GREAT SOUND MAKES NO NOISE®

## CROSSNET-ONE™ SOUND MASKING SYSTEM

### Platform-Net Specifications – Model #BP-Net

When a networked direct fired speaker or system is required, the Lencore CrossNetOne™ system provides the highest level of sound quality and adjustability and offers the ability for network control. Through the system's managing software, zones can be created and modified for masking and paging. On-going changes and additions to zones can all be handled through the network interface without the need to rewire the system.

Random sound masking source, coupled with Lencore's E-Sound™ technology provide capabilities for:

- Attenuation Adjustments: 96 in ½ dB steps
- Contour Adjustments: 29 steps

Volume and contour adjustments can be made via the network simply and easily and uploaded to the system for immediate results. The system is also tunable by hand-held remote. Lencore is the only sound masking company that can offer both 3.5" and 6" speakers that offer the widest dispersion and best sound quality for direct fired systems.



Platform-Net is UL Listed and approved for use in air-handling spaces.

### Sound Source: The Platform-Net

The heart of the CrossNetOne™ system is the Platform-Net, the primary sound source that produces, equalizes and distributes the sound for masking, music and paging. Each Platform-Net includes:

- Random sound masking source, coupled with Lencore's E-sound™ technology, produce a sound quality that is random, making it exceptionally comfortable environment.
- Independent equalizers for unprecedented tuning where every channel of the system has a separate and independent 1/3<sup>rd</sup> octave band equalizer or parametric equalizer. Sound frequencies and contour can be adjusted and set to any point on the acoustical curve, from 20 Hz to 20 kHz, making the CrossNetOne™ the first networked sound masking system to make fine-tuning the entire spectrum of sound possible.

The network is intelligent enough to bypass any failure in the system to keep communicating throughout the entire network. Competitor's point-to-point networks can not achieve this level of connectivity and diagnostic control.

### Additional Platform-Net Features and Capabilities:

- Gathers instructions from the remote control or i.LON® and sends information and directions up to 199 Platform-Nets within the network for system tuning and modifications.
- Displays information on its integrated LCD screen, including the specific address of the respective enclosure. This address aids in locating the correct Platform-Net in the ceiling plenum, and eliminates the need for as-built drawings when checking or modifying the system.
- Checks (during a diagnostic test) each Platform-Net for system performance, including the operation of the network, program, memory, power, and characteristics of sound masking.

### Extreme Flexibility:

CrossNetOne's™ sound source and channels let you customize an almost limitless amount of zones for masking, paging and music, while maintaining the advantages of complete networked operation and control.

i.LON® is a registered trademark of Echelon Corporation.

Lencore Acoustics Corp. • 1 Crossways Park Drive West • Woodbury, NY 11797 • (P) 516-682-9292 • (F) 516-682-4785 • email: [info@lencore.com](mailto:info@lencore.com)  
Spectra i.Net™, Spectra™, CrossNetOne™, CrosswaysOne™ are trademarks of Lencore Acoustics Corp. All rights reserved.

© Copyright 2009

## CROSSNET-ONE™ SOUND MASKING SYSTEM

### Platform-Net Specifications – Model #BP-Net (page 2)



## TECHNICAL SPECIFICATIONS

**Enclosure:** Platform-Net enclosure is brushed aluminum  
**Dimensions:** 10" x 7" x 1 7/8"

### Noise Generator:

- Octave bands from 25Hz to 20,000Hz
- Parametric bands from 20Hz to 20,000Hz
- Voltage: 48 Volts DC
- Contour Adjustments
- Spectrum adjustment shall meet acoustical preferred curve

### Spectrum Shaping:

- Units are able to be shaped with a 1/3 band octave equalizer
- Units are able to be shaped with a parametric equalizer
- Equalizers cover the full spectrum to manipulate the entire spectrum from 20Hz to 20KHz

### Wire Requirements:

16 gauge, plenum rated, stranded, 2-conductor wire (for power supply to Platform-Net)

Cat 5e cable or equivalent, 3 and 4 twisted pair, with standard RJ12 & RJ45 connectors.

- 3 twisted pair (audio cable and speaker cable)
- 4 twisted pair (data cable)

### Remote Infra-Red Volume and Contour Control:

Immediate volume and contour control adjustments for masking, paging and music. Point the remote to a wall mounted, infrared receiver panel or directly at an individual Platform-Net.

### Paging Input:

INPUTS

Telephone page input  
Program input  
Aux input

- Input sensitivity and impedance 600 ohms, balanced.
- MPI PBX Trunk Power 7.5V, 4AMPs

### Paging Equipment:

If paging option is required, see product sheet for Lencore's Music Page Interface (MPI).

Masking/Paging Units are UL Listed for use in air handling spaces

### Output Adjustments:

- 1/3 octave band EQ for entire spectrum (25Hz- 20KHz). Meets ANSI specification for bands.
- Parametric EQ for entire spectrum (20Hz-20KHz).
- Volume control for individual channels, groups/zones, or global for sound masking, paging and music.
- Contour control for individual channels, groups/zones or global for sound masking.
- EO control for individual Platform-Net's or global for page/music.
- EO control for individual channels, groups/zones or global for sound masking.
- Programming of groups and zones.

### Integration of Separate Page and Music Channels:

Each channel can be digitally controlled for zone management and changed on the fly without any change in wiring.

### Program Memory:

Nonvolatile for one year minimum, without power. When re-energized after a power outage, control starts last saved savings.

### Other Systems Also Available

Spectra i.Net™ (Networked), Spectra®, CrossNetOne™ (Networked), CrosswaysOne™

In-plenum and direct fired all available with page/music.