

Lencore

THE LEADING MANUFACTURER OF SOUND MASKING SYSTEMS.

A GREAT SOUND MAKES NO NOISE®

CROSSNET-ONE™ SOUND MASKING SYSTEM

Remote Control Specifications – Model #G16

When a networked direct fired speaker or system is required, the Lencore CrossNetOne™ system provides the highest level of sound quality and adjustability and offers the ability for network control. Through the system's managing software, zones can be created and modified for masking and paging. On-going changes and additions to zones can all be handled through the network interface without the need to rewire the system.

Random sound masking source, coupled with Lencore's E-Sound™ technology provide capabilities for:

- Attenuation Adjustments: 96 in ½ dB steps
- Contour Adjustments: 29 steps

Volume and contour adjustments can be made via the network simply and easily and uploaded to the system for immediate results. The system is also tunable by hand-held remote. Lencore is the only sound masking company that can offer both 3.5" and 6" speakers (height 6" and 4") that offer the widest dispersion and best sound quality for direct fired systems.

The CrossNetOne's™ hand-held remote control enables end users to make immediate volume and contour control adjustments for masking, paging and music. Point the remote to a wall mounted, infrared receiver panel or directly at a Platform-Net.



Remote size: 2" w x 3.5" h
Thickness: ¼"

TECHNICAL SPECIFICATIONS

Molded plastic slim style hand held remote adjusts volume and contour for masking, music and paging at BP-Net location by channel. Also can be configured to use at a designated wall location if desired.

Remote construction: Molded plastic rubber coated resin adjustment buttons.

Size: 2" w x 3.5" h
Thickness: ¼"

Battery Replacement:
Replace battery with a 3V CR2025 Lithium battery.

Other Systems Also Available

Spectra i.Net™ (Networked), Spectra®, CrosswaysOne™

In-plenum and direct fired
all available with page/music.