

Lencore

THE LEADING MANUFACTURER OF SOUND MASKING AND ACOUSTICAL PANEL SOLUTIONS.

A GREAT SOUND MAKES NO NOISE®

LENCORE CROSSWAYS™ SOUND MASKING SYSTEM

Direct Field Remote Control Specifications – Model BP16

When a direct field speaker or system is required due to site conditions or application need, the Lencore Crossways™ system provides the highest level of sound quality and adjustability. With its higher quality construction, Crossways™ offers a refreshing, commercial grade alternative to the retail quality products other competitive systems have offered previously.

Tunable by hand-held remote and available in small and larger speaker sizes. Crossways™ offers wider sound dispersion, and better sound uniformity and greater sound quality.

Multiple random sound masking sources, coupled with Lencore's E-Sound™ technology provide capabilities for:

- Masking Adjustments: 96 in ½ dB steps
- Contour Adjustments: 29 steps

Installation is simplified using plug and play Cat 5e cable with standard RJ12 connections. The Crossways™ speaker is equipped with dog ear screw adjustments and a locator pin to insure a smooth installation.



Remote size: 2" w x 3.5" h
Thickness: ¼"

TECHNICAL SPECIFICATIONS

Molded plastic slim style hand held remote adjusts volume and contour for masking, music and paging at BP location by channel. Also can be configured to use at a designated wall location if desired.

Remote construction: Molded plastic rubber coated resin adjustment buttons.

Size: 2" w x 3.5" h
Thickness: ¼"

Battery Replacement: Replace battery with a 3V CR2025 Lithium battery.

Other Systems Also Available

Spectra i.Net™ (Networked), Spectra®, CrossNet™ (Networked), Crossways™

In-plenum and direct field
all available with paging/music.