

i.Net

STANDARD SPEAKER

MODELS GP19gsa/GP85gsa



FUNCTION

What makes Lencore's i.Net system intelligent is its intuitive technology and its infinite flexibility on an open-platform system to suit any project size. The combined innovations of the complete sound masking system – sound source, speakers, power supply; i.LON, music page interface, equalizers, online System Manager control and one-touch remote control put the i.Net system on a new level of customization and performance.

The i.Net system is the most sophisticated masking system available when a network system is required. The system features fast, complete control over every sound frequency for masking. Extreme design flexibility, plus, easy system expansion with the addition of sound sources and speakers to the network. Sound control with the click of the remote or mouse, even off-site. Preferred, award-winning sound quality, only from Lencore's Systems. Speakers are configured with integrated RJ12 connections for plug & play and ease of installation.

* MASKING/PAGING UNITS ARE UL LISTED FOR USE IN AIR HANDLING SPACES

SPEAKER ENCLOSURE

- + Aluminum Housing
- + Galvanized Perforated Grill
- + Lightweight Mounting Chain
- + Two speaker size available: 6" & 4"
- + Height: 6" GP19gsa 4" GP85gsa
- + Diameter: 6" GP19gsa 6" GP85gsa
- + Weight: 3 lbs. GP19gsa 3 lbs. GP85gsa

LOUDSPEAKER

- + 5-inch wide dispersion
- + Power Rating: 10 watts RMS
- + Frequency Response:
- + 50 – 12,000 Hz
- + Impedance: 32 Ohms
- + Resonance: 80 Hz
- + Magnet Weight: 10 oz.
- + Magnet Structure Weight: 26 oz.
- + Cone: Formed Fiber
- + Cone Suspension: High Compliance Foam
- + Voice Coil: 1-inch diameter
- + Voice Coil Form: Anodized Aluminum

PRODUCT SHEET & SPECIFICATIONS

i.Net STANDARD SPEAKER

MODELS GP19gsa/GP85gsa

GENERAL SPECIFICATIONS

- + Paging Input: via OP and MPI
- + Power Requirement: Powered by OP
- + Output Adjustment: N/A

WIRE REQUIREMENTS

- + All wire must be plenum rated and UL listed.
- + Speakers use Cat 5e or equivalent, 3 twisted pair and RJ12 connectors.
- + Crossover wire: Pin 1 to Pin 6, Pin 2 to Pin 5, etc

OTHER SYSTEM REQUIREMENTS

- + 16 gauge, plenum rated, stranded, 2-conductor wire (for power supply to OP).
- + Cat 5e cable, 3 twisted pair, with standard RJ12 connectors.
- + 3 twisted pair (audio cable and speaker cable)

Masking/Paging Units are UL Listed for use in air handling spaces