

i.Net

OUTDOOR PAGING SPEAKER

MODEL WPSPKR-15



FUNCTION

The Outdoor Paging Speakers are compact two-way speaker systems designed for high efficiency, wide range, and high power input handling capability. These speaker systems can be installed in a manner ideal for the location and intended application.

FEATURES AND CAPABILITIES

- + 90° horizontal x 90° vertical wide directivity high-frequency horn.
- + Supplied bracket permits mounting to a wall, ceiling, or an optional speaker stand.
- + Feature a waterproof design (IPX4 standard) for protection from any adverse effects of outdoor installations.

SPEAKER MODEL DIMENSIONS/WEIGHT

- + 130 (w) x 202 (h) x 131 (d) mm
- + 2kg

ENCLOSURE TYPE

- + Bass-reflex type

MESH SPEAKER GRILL

- + Surface-treated steel plate, black, anti-rust paint

WATER RESISTANCE

- + IPX4

INPUT TERMINALS

- + Push in Terminals

FREQUENCY RESPONSE

- + 85 – 20,000 Hz, –10 dB at installation in a semianechoic field

DIRECTIVITY ANGLE

- + Horizontal: 90°, Vertical: 90°

POWER HANDLING CAPACITY

- + 15W

SPEAKERS

- + Woofer: 10 cm cone-type
- + Tweeter: balanced dome-type

CROSSOVER FREQUENCY

- + 5 kHz

OPERATING TEMPERATURE

- + -10 °C to +50 °C

OUTPUT SOUND PRESSURE LEVEL

- + 87 dB (1 W, 1 m) at installation in a semianechoic field

RATED IMPEDANCE

- + 670 Ω (15 W), 2 kΩ (5 W), 3.3 kΩ (3 W), 10 kΩ (1 W)

