

## PRODUCT SHEET & SPECIFICATIONS

# n.FORM™

## DECORATIVE FIXED MOUNT ROUND SPEAKER

MODELS G865-W/G865-B

\*W = white B = black



### FUNCTION

n.FORM™ was innovated to provide superior performance in Mass Notification and Emergency Communication (MNEC) solutions. n.FORM delivers a clearer, more intelligible message and audio signal and offers greater control and flexibility - ultimately delivering a smarter and more secure system.

The wall mounted Pendant Speaker offers a decorative, direct fired option when aesthetics is a concern. With more open environments and exposed ceilings becoming the norm, a decorative solution for sound masking and Mass Notification has been difficult to find. The speaker is constructed of high quality plastic, delivers the superior sound quality Lencore is known for, and is easy to install. The speakers can be mounted to the ceiling, a wall, or a beam and allow for Cat5e connections directly to the speaker.

### SPEAKER ENCLOSURE

- + Plastic Housing
  - G890-W: White Housing
  - G890-B: Black Housing
- + Grill: Metal screen, white or black with perforated grill
- + Wall Bracket: plastic

### SPEAKER COVERAGE

- + 100 sq. ft. (nominal 10' speaker separation)

### LOUDSPEAKER

- + Power Rating – 10 watt continuous, 20 watt peak
- + Frequency Response – 90-18 kHz
- + SPL for Masking Output: 90 dB
- + Impedance – 32 Ohms
- + Speaker Weight – 1.1 lbs
- + Overall Speaker Dimension – 4 3/4" (not including bracket)

### AGENCY LISTINGS

- + UL1480

## PRODUCT SHEET & SPECIFICATIONS

### n.FORM™ SPEAKERS

MODEL LG035-G655 / LG035-G654 / LG035-G656-INLINE

#### PAGING INPUT

+ Via OP & MPI-6

#### POWER REQUIREMENT

+ Powered by OP

#### WIRE REQUIREMENTS

- + All wire must be plenum rated and UL listed
- + Speakers use Cat 5e or equivalent, 4 twisted pair and RJ45 connectors
- + Straight cable – Pin 1 to Pin 1, Pin 2 to Pin 2, etc

#### OTHER SYSTEM REQUIREMENTS

+ 16 gauge, plenum rated, stranded, 2-conductor wire (for power supply to OP)