

PRODUCT SHEET & SPECIFICATIONS

n.FORM™

DECORATIVE PENDANT/INLINE SPEAKER

MODELS G890-W / G890-B INLINE: G890-INLINE-W / G890-INLINE-B

*W = white B = black



FUNCTION

n.FORM™ was innovated to provide superior performance in Mass Notification and Emergency Communication (MNEC) solutions. n.FORM delivers a clearer, more intelligible message and audio signal and offers greater control and flexibility - ultimately delivering a smarter and more secure system.

The Pendant Speaker offers a decorative, direct fired option when aesthetics is a concern. With more open environments and exposed ceilings becoming the norm, a decorative solution for sound masking, paging and Mass Notification has been difficult to find.

The speaker is constructed of high quality plastic, delivers the superior sound quality Lencore is known for, and is easy to install. The Pendant Speaker comes with a gem box for Cat5e connections at the deck location which minimizes cable exposure for the client.

*The inline speaker option also provides an additional volume control with a remote attenuator. 0 to -12dB adjustments can be made from the remote.

SPEAKER ENCLOSURE

- + Plastic Housing
 - G890-W: White Housing
 - G890-B: Black Housing
 - G890-INLINE-W: White Housing
 - G890-INLINE-B: Black Housing
- + Grill: Metal screen, white or black with perforated grill

SPEAKER COVERAGE

- + 100 sq. ft. (nominal 10' speaker separation)

LOUDSPEAKER

- + Power Rating – 10 watt continuous, 20 watt peak
- + Frequency Response – 90-18 kHz
- + SPL for Masking Output: 90 dB
- + Impedance – 32 Ohms
- + Speaker Weight – 1.1 lbs
- + Overall Speaker Dimension – 5.3"

AGENCY LISTINGS

- + UL1480

PRODUCT SHEET & SPECIFICATIONS

n.FORM™ SPEAKERS

MODEL LG035-G655 / LG035-G654 / LG035-G656-INLINE

PAGING INPUT

+ Via OP & MPI-6

POWER REQUIREMENT

+ Powered by OP

WIRE REQUIREMENTS

- + All wire must be plenum rated and UL listed
- + Speakers use Cat 5e or equivalent, 4 twisted pair and RJ45 connectors
- + Straight cable – Pin 1 to Pin 1, Pin 2 to Pin 2, etc

OTHER SYSTEM REQUIREMENTS

+ 16 gauge, plenum rated, stranded, 2-conductor wire (for power supply to OP)