

AMPLIFIER

PRODUCT SHEET & SPECIFICATIONS

POWER AMPLIFIER

(MODEL APFR-300,
APFR-2CH1000, APFR2CH-1500)



- DESCRIPTION

The APFR-300, APFR-2CH1000 and APFR-2CH1500 provides exceptional performance and flexibility for installed sound applications. The amplifiers feature independent selection of high and low impedance operation for a specific channel, plus power levels and features that were carefully chosen to match the requirements of fixed install design.

- FEATURES AND CAPABILITIES

- + High power-density + 2 channels in a 2U chassis.
- + Direct constant-voltage (70V/100V/140V/200V) or low-impedance (2/4/8/ ohm) operation.
- + Input sensitivity Independently selectable for each channel.
- + TLC protection circuitry protects the amplifier from long-term excessive heat by subtly and dynamically reducing the gain only when necessary.
- + Switchable high-pass filter for each channel provides low-frequency roll off to eliminate step down transformer saturation when used in distributed systems.
- + Comprehensive array of indicators including Power, Data and Bridge, along with Ready, Signal, Clip, Thermal and Fault for each channel, provide accurate diagnostics.

AMPLIFIER

Model

APFR-300
APFR2CH-1000
APFR2CH-1500

- Specifications

	APFR-300	APFR2CH-1000	APFR2CH-1500
Channels	2	2	2
Sensitivity	1.4V	1.4V	1.4V
Signal to Noise Ratio (below rated power 20Hz to 20kHz, A-Weighted)	105dB	105dB	105dB
Total Harmonic Distortion (THD) (full rated power, 20Hz - 20kHz)	< 0.1%	< 0.35%	< 0.35%
Damping Factor (10 Hz to 100Hz)	<3000	<3000	<3000
Frequency Response (at 1W into 4/8 ohms)	± 0.25dB	± 0.25dB	± 0.25dB
Crosstalk (below rated power 20Hz to 1kHz)	> 80dB	> 80dB	> 80dB
Common Mode Rejection (20Hz to 1Khz)	> 50dB	> 50dB	> 50dB
Maximum Input Level (before input compression)	+20dBu	+20dBu	+20dBu
Load Impedance	70V, 100V (2-16 Ohms)	70V, 100V (2-16 Ohms)	70V, 100V (2-16 Ohms)
Voltage Gain (at maximum level settings) (8/4 ohm operation)	35:1 (31dB)	35:1 (31dB)	35:1 (31dB)
Power Draw at Idle (120VAC mains: standby mode) -	24W	35W	35W

- General

Dimension (H x W x D)	3.5" x 19" x 14.25"	3.5" x 19" x 14.25"	3.5" x 19" x 14.25"
Net Weight	22.8 lbs	22.8 lbs	22.8 lbs
Net Shipping Weight	27.7 lbs	27.7 lbs	27.7 lbs

V1.0

Lencore Acoustics Corp. One Crossways Park Drive West Woodbury, NY 11797 p 516-682-9292 f 516-682-4785 info@lencore.com
Spectra i.Net®, Spectra®, n.FORM™, Spectra Tangent® are trademarks of Lencore Acoustics Corp. All rights reserved. © Copyright 2014

 **LENCORE**
MANUFACTURER. INNOVATOR. LEADER.

AMPLIFIER

Model

APFR-300 APFR2CH-1000 APFR2CH-1500

APFR-300

20 Hz–20 kHz
Power

2-ohm Dual (per ch.)	150W
4-ohm Dual (per ch.)	300W
8-ohm Dual (per ch.)	300W
16-ohm Dual (per ch.)	300W
70V Dual (per ch.)	300W
100V Dual (per ch.)	* 300W
4-ohm Bridge	300W
8-ohm Bridge	600W
16-ohm Bridge	600W
100V Bridge	* 600W
140V Bridge	600W
200V Bridge	* 600W

20 Hz–20 kHz Power refers to maximum average power in watts from 20 Hz to 20 kHz with 0.1% THD.

* With T-170V or TP-170V.

APFR-2CH1000

20 Hz–20 kHz
power

2-ohm Dual (per ch.)	1000W
4-ohm Dual (per ch.)	1000W
8-ohm Dual (per ch.)	1000W
16-ohm Dual (per ch.)	625W
70V Dual (per ch.)	1000W
100V Dual (per ch.)	1000W
4-ohm Bridge	2000W
8-ohm Bridge	2000W
16-ohm Bridge	2000W
140V Bridge	2000W
200V Bridge	2000W

20 Hz–20 kHz Power refers to maximum average power in watts from 20 Hz to 20 kHz with 0.35% THD.

AMPLIFIER

Model

APFR-300
APFR2CH-1000
APFR2CH-1500

APFR-2CH1500

20 Hz–20 kHz
POWER

2-ohm Dual (per ch.)	1500W
4-ohm Dual (per ch.)	1500W
8-ohm Dual (per ch.)	1250W
16-ohm Dual (per ch.)	625W
70V Dual (per ch.)	1500W
100V Dual (per ch.)	1500W
4-ohm Bridge	3000W
8-ohm Bridge	3000W
16-ohm Bridge	2500W
140V Bridge	3000W
200V Bridge	3000W

20 Hz–20 kHz Power refers to maximum average power in watts from 20 Hz to 20 kHz with 0.35% THD.