

PRODUCT SHEET AND SPECIFICATIONS

PAGING HORN (PG-HRN-15)



FUNCTION

Lencore's decorative paging horns are available when a surface-mounted speaker is desired or necessary due to site configuration or condition.

The decorative paging horns are typically specified in areas where the ambient background noise is already greater than 50 dB. These areas might include cafeteria areas where no ceiling tile is present.

These decorative paging horns have a dispersion of 70° H x 90° V.

Paging speakers are also available for offices, conference rooms, public areas, cafeterias, and other enclosed areas where aesthetics is a concern. Please ask your Lencore representative for more information on this option.

Specify Model # PGHRN-40WP for outdoor use or similar conditions, where weather resistance is required.

SPEAKER MATERIAL:

- + Horn Flare: Aluminum, off-white, Powder Coating
- + Reflector Horn and Rear Cover: ABS Resin, Off-White

SPEAKER SIZE: 8.74" x 7.04" x 9.21"

WEIGHT: 2.43 lbs.

POWER HANDLING: 15 W

LOUDSPEAKER:

- + SPL (1W/1m, 500 Hz to 2,500 Hz): 112dB SPL
- + Dispersion: 70° H x 90° V
- + Frequency Response: 280 Hz – 12.5 kHz

GENERAL SPECIFICATIONS:

- + Paging Input: via OP and MPI
- + Power Requirement: Powered by OP
- + Output Adjustment: N/A