

Paging Horn

MODEL INETHRN-15



FUNCTION

Lencore's decorative paging horns are available when a surface-mounted speaker is desired or necessary due to site configuration or condition.

The decorative paging horns are typically specified in areas where the ambient background noise is already greater than 50 dB. These areas might include cafeteria areas where no ceiling tile is present.

This paging horn can be wired directly to Lencore's Operating Platform with up to 2 horns per channel. An external amplifier is not required.

SPEAKER MATERIAL:

- + Horn Flare: Aluminum, off-white, Powder Coating
- + Reflector Horn and Rear Cover: ABS Resin, Off-White

SPEAKER SIZE: 8.74" x 7.04" x 9.21"

WEIGHT: 2.43 lbs.

POWER HANDLING: 15 W

LOUDSPEAKER:

- + SPL (1W/1m, 500 Hz to 2,500 Hz): 112dB SPL
- + Dispersion: 70° H x 90° V
- + Frequency Response: 280 Hz – 12.5 kHz

GENERAL SPECIFICATIONS:

- + Paging Input: via OP and MPI
- + Power Requirement: Powered by OP
- + Output Adjustment: N/A

WIRE REQUIREMENTS

- + All wire must be plenum rated and UL listed
- + Speakers use Cat 5e or equivalent, 4 twisted pair and RJ45 connectors, 568B wiring